

JAX GRINDER-GLIDE FREE

NSF 3H Lubricant for Meat Grinding Equipment

PRODUCT DESCRIPTION

JAX Grinder-Glide Free is a direct food contact grinder lubricant. In many meat grinding applications, two lubricants are commonly used: one after the sanitization process as a rust and corrosion inhibitor and one as a start-up lubricant to provide protection to the grinder plates and knives. JAX Grinder-Glide Free eliminates this two-step process by providing a direct food contact lubricant that has unmatched rust and corrosion protection as well as the load carrying and lubricity properties necessary to eliminate dry start ups.

JAX Grinder-Glide Free is compounded exclusively from carefully selected base oils that eliminate MOSH/MOAH concerns and from additives that are Generally Recognized As Safe (GRAS) and/or safe for human consumption.

PRODUCT BENEFITS

- **Direct-contact** — JAX Grinder-Glide Free can be used in a food processing environment where direct food contact is inevitable.
- **Prevents dry start-up** — During the meat grinding process, the fat from the meat provides the lubrication necessary to minimize grinder plate wear. However, during the initial start-up period, there is no natural meat fat coating the grinder plates to provide this protection. JAX Grinder-Glide Free provides the lubricity and load carrying strength necessary to protect and maintain your grinder plates.
- **Superior additive performance** — JAX Grinder-Glide Free is formulated to provide superior rust and corrosion protection, outstanding metal wetting characteristics, and excellent lubricity to minimize downtime and maximize grinder life.
- **MOSH/MOAH-Free** — Contains no MOSH/MOAH content, limiting exposure concerns with saturated and aromatic hydrocarbons on food product.
- **NSF 3H-Registered**
- **Kosher Pareve Certified**



APPLICATIONS

- Grinding equipment where direct food contact is unavoidable



jax.com



TYPICAL PROPERTIES	GRINDER-GLIDE FREE	METHOD
Viscosity at 40°C, cSt	24.8	ASTM D 445
Flash Point, °C	213.5	ASTM D 93
Specific Gravity	0.9373	ASTM D 1298
Four Ball Wear, mm	0.41	ASTM D 4172

JAX products undergo continual improvement in formulation and manufacture. The values indicated in this PDS are typical production values at the time of this writing. JAX reserves the right to alter and update product data and typical values at any time without notice. It is the responsibility of the installer and/or purchaser to determine if these specifications are adequate and proper for the intended application. MSDS information may be found at JAX.com or by contacting JAX INC.

COMPATIBILITY

JAX Grinder-Glide Free is formulated to be compatible with metallurgies typically seen in trolleys and overhead chains.

PACKAGING

CONTAINER SIZE	GRINDER-GLIDE FREE
55 Gallon Drum	GGFREE-055
5 Gallon Pail	GGFREE-005